

FHI 3500



TECHNICAL DATA

- Maximum Out-Put: 12 l/min.
- Minimum Out-Put: 1 l/min.
- Max Hydraulic Pressure: 400 BAR
- Max Working Pressure: 270 BAR
- Electrical Power req.: 15 Kw - 380V 3ph
- Transformer: 4000 VA
- Max Hoses Length: 100 meters

STANDARD EQUIPMENT

- Mt.25 (82") Heated Hoses FUTURA 1/4"
- N° 2 Air Driven Transfer Pumps 3:1 (ratio)
- Recycling valves & tubes

STANDARD FEATURES

- Parallel Pumps with adjustable ratio 100:100 by volume
- Automatic washing system in the ISO side
- Separate preheaters for maximum efficiency
- Material supply filters to avoid failure in ball valves
- Max pressure Cut-Off valves in both sides for safety
- Manual valves for fast recycling
- Electronic control for ISO & POLY pre-heaters
- Separate electronic control for ISO & POLY on heated hoses
- Easy replacement of pumps for easy maintenance
- N.4 Wheels for easy moving
- Support for transfer pumps
- FUTURA FT3 Spray Gun



www.futuraeurope.com



FUTURA EUROPE srl
Contrada Torbidello 26
63071 ROTELLA (AP) - Italy

Headquarters
Viale Sacco e Vanzetti 13
63827 PEDASO (FM) - Italy

Tel. +39 (0) 734 933227
Fax +39 (0) 734 917037
info@futuraeurope.com





FHI 3500



**PROPORTIONING
SPRAY MACHINE
FIX RATIO 1:1
FOR POLYUREA &
POLYURETHANES**